Carrymate® Transport Grips



The unloading and transportation of sheet materials to their installation sites is not only time-consuming but also very strenuous. Smooth surfaces make it difficult to securely carry the material, especially through narrow passages or across uneven grounds. Carrymate® Transport Grips are used in pairs and each grip is capable of lifting up to 100 kg, which makes them suitable for moving a wide variety of materials

- · the point of contact to the material can be wherever it is most suitable for
- · both users can walk forward and face the direction they are going in
- the user´s lifting arm remains straight and thereby more relaxed
- the user 's other hand is now free to support the material or to move obstacles to the side (open doors, etc.)
- experience heavy lifting that saves you time and is easy on your back

The clamping system self-adjusts to the width of the material and securely holds it in place without damaging its surface. All parts of the Carrymate® Transport Grips that touch the load are covered with a special coating so that even the most polished materials will not be scratched. The ergonomically designed carrying grip provides a













secure hold and even during turns and swivels the user can easily hold on to the

Description Application Accessories

Carrymate® Transport Grips

- Sturdy aluminium construction
- Selfadjusting Clamps
- · Lifts up to 100kg (220 lbs.) per grip
- · Sold in pairs
- · Absolutely slip-proof
- Cushioned shaft prevents damage to the carried load



CARRYMATE 5 span width 0-80 mm



CARRYMATE Senior span width 40-120 mm



CARRYMATE XL span width 80-160 mm

Carrymate® T-GRIPS

The non-slip CARRYMATE $^{\otimes}$ T-Grips enable four users to carry heavy loads, allowing for a more even weight distribution with two operators per grip. The self-adjusting clamps are available in three sizes for different material widths and each set of grips can hold up to 440lbs. The grips are ergonomically designed to help the users safely lift heavy loads.



Carrymate TG 80 span width 0-80 mm



Carrymate TG 120 span width 40-120 mm



Carrymate TG 160



















